



Product information

INDUcoder MANUAL ENCODER
HANDY PULSER EHP-LS

Electronic hand-held terminal

Enable switch

Switch for axis selection „X, Y, Z, 4“

Switch for factor „x1, x10, x100“

Very flat housing - case height only 31 mm

Spiral cable with 2, 3 or 5 m length

High protection class IP 65

The well established INDUcoder product line of manual pulse generators and hand-held terminals has been expanded to a new device, the **HANDY PULSER EHP-LS**.

The electronic hand-held terminal pulser box is made of ABS synthetic. The very flat case height of only 31 mm leads to a very handy device. The built-in rotating knob with mechanical click-stop is comparable to manual pulse generator ESO 77 and is available with resolutions of 25 or 100 pulses per revolution.

Supply voltage is available with the following combinations:

5 VDC with RS422 line driver or

5 – 12 VDC with open collector output with internal pull-up resistor.

HANDY PULSER EHP-LS provides one switch for selecting the axis „X, Y, Z, 4“ and one switch for factor selection „x1, x10, x100“. The enable switch avoids erroneously changing of the above mentioned settings and increases safe operating with the terminal. The hand-held terminal is available with 2, 3 or 5 m spiral cable.

HANDY PULSER EHP-LS has a high protection class of IP 65 and is especially suitable for rough environmental conditions.

INDUcoder Messtechnik GmbH
Kaiserstrasse 316 - 47178 Duisburg - Germany

phone: +49 203 / 57047-0
fax: +49 203 / 57047-20

Internet: <http://www.inducoder.de>

E-Mail: info@inducoder.de